

Polydoros RFX

oem-products.siemens-healthineers.com



Features and benefits

Polydoros RFX

System Integration

- DR protocol, supported by leading DR workstation providers, assures fast integration into your system
- Compatible with tubes from Siemens
- Small Footprint/Volume of ~ 100 l

User Interface

- Mini console designed for easy disinfection
- DR protocol enables full remote control via DR workstation
- Web interface for Service

Business Support

- Pre & After Sales Support combined with integration support
- Fast spare part delivery world wide for your business
- Hotline assistance for universal services
- Less inventory, because of scalable architecture



Type and material number

| Model | Power rating | Material number | |
|--------------------------|----------------|-----------------|--|
| Polydoros RFX Low Power | 30/40/55/65 kW | 11011802 | |
| Polydoros RFX High Power | 80 kW | 11011803 | |

Technical data

| Nominal power* | 55 and 65 kW | 80 kW (2 INV) | |
|---------------------|--|-----------------|--|
| kV range | 40 kV to 150 kV | | |
| kV steps | 1 kV Steps | | |
| mA range | 10 to 800 mA | 10 to 1000 mA | |
| mAs range | 0.5 to 800 mAs | 0.5 to 1000 mAs | |
| Exp. time range | 1 ms to 5 s | | |
| HV rise time | ≤1 ms** @ ≤150 kV | | |
| X-ray tube support | Siemens Healthineers RAY®-14 Siemens Healthineers RAY®-12 Siemens Healthineers SDR 150/30/55-3 Siemens Healthineers SV 150/40/80C-100 | | |
| No. of workstations | 3: BWS, table, free exposure | | |
| Modes of operation | 1 point with falling load; 2 and 3 point (constant load) | | |
| AEC chamber | Siemens Healthineers 3 and 5 field shadow free chamber | | |
| Web interface | For service | | |
| Mini console | On/off, exposure, disinfection possible | | |
| Volume / dimensions | ~100 I/602 × 374 × 442 mm/< 78 kg | | |
| Line voltage | 380-480 V/3~ | | |
| EMC Class | B; for residential and rural areas | | |
| | | | |

^{*} R&D pointed out: Reduction of Power not possible in VA21 and VA22, no mechanism implemented

^{**} For the kV voltage range from 50–80 kV for tube currents It > 850 mA, the rise time is < 2ms.

This document is not considered to be a contractual specification. Kindly contact Siemens Healthineers prior to using this information for equipment design.

These components and configurations are not finished medical devices. Compliance with all laws and regulations that are applicable to finished medical devices is the responsibility of the assembler/manufacturer of the finished medical device.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases. The required features should therefore be specified in each individual case at the time of closing the contract.

This component does not contain any substances that exceed the limitations defined in the Directive 2011/65/EU, Annex II, on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

Technical data provided in this document may vary within defined tolerances. Original images always lose a certain amount of detail when reproduced.

The components are maybe branded "Siemens Healthineers". However, the purchaser shall not market the components using the "Siemens Healthineers" brand name and/or trademark. The purchaser may integrate these components into a system using its own brands and labels. The product names and/or brands referred to are the property of their respective trademark holders.

This document shall not be made available to healthcare professionals or to the general public.

The Technology Centers of Siemens Healthineers AG (TCs)/ Siemens X-Ray Vacuum Technology Ltd., Wuxi, are ISO 13485 certified. Components and products are manufactured in accordance with the Quality System Regulations (QSR) as defined by the U.S. Food and Drug Administration (FDA). The TCs endeavor to comply with legal requirements concerning the environmental compatibility of their products.

The reproduction, transmission or use of this document or its contents is not permitted without express written consent. Offenders will be liable for damages.

Siemens Healthineers reserves the right to modify the design and specifications contained herein without prior notice. All rights reserved, particularly in connection with patent applications or registrations of utility model or design.

Siemens Healthineers Headquarters

Siemens Healthineers AG Siemensstr. 3 91301 Forchheim, Germany Phone: +49 9191 18-0

Phone: +49 9191 18-0 siemens-healthineers.com

Manufacturer

Siemens Healthcare GmbH Henkestr. 127 91052 Erlangen, Germany

Local Contact Information in Germany

Siemens Healthineers AG
Technology Excellence
Power & Vacuum Products
An der Laende 3–9
91301 Forchheim, Germany
oem.func@siemens-healthineers.com
oem-products.siemens-healthineers.com

Publisher for USA

Siemens Medical Solutions USA, Inc. 40 Liberty Boulevard Malvern, PA 19355 United States of America